

List 1 HTS	Excluded Description
8402.90.0010	Heat exchangers, the foregoing comprising parts of goods of heading 8402 and each fitted for heat recovery generator (described in statistical reporting number 8402.90.0010)
8412.29.8045	Hydraulic powered swing, winch and travel drives, axial piston type, with attached gearboxes, each valued over \$2,000 but not over \$7,000 (described in statistical reporting number 8412.29.8045)
8413.19.0000	Lubricating oil transfer pumps, fitted or designed to be fitted with a measuring device, each with a 1.5 kW motor (described in statistical reporting number 8413.19.0000)
8413.50.0010	Oil well and oil field reciprocating positive displacement plunger pumps (described in statistical reporting number 8413.50.0010)
8413.50.0090	Positive displacement piston liquid pumps designed for use with gas or electric powered pressure washers, rated for an output of 7 liters or more but not exceeding 16 liters per
8413.60.0090	Non-hydraulic rotary positive displacement pumps, not configured as roller pumps, each weighing less than 5.5 kg and valued not over \$25 (described in statistical reporting number 8413.60.0090)
8413.70.2004	Submersible centrifugal pumps (other than fuel, lubricating or cooling medium pumps for internal combustion piston engines other than stock pumps imported for use with machines for making cellulosic pulp, paper or paperboard), not fitted or designed to be fitted with a measuring device; each of the foregoing incorporating a magnetic drive motor (described in statistical reporting number 8413.70.2004)
8413.70.2004	Submersible centrifugal pumps (other than fuel, lubricating or cooling medium pumps for internal combustion piston engines), not fitted or designed to be fitted with a measuring device, the foregoing for table-top decorative use incorporating a cascading water feature (described in statistical reporting number 8413.70.2004)
8413.70.2004	Submersible centrifugal pumps (other than fuel, lubricating or cooling medium pumps for internal combustion piston engines; other than stock pumps imported for use with machines for making cellulosic pulp, paper or paperboard), not fitted or designed to be fitted with a measuring device, the foregoing capable of operating at 3,700 liters or more but not exceeding 41,000 liters per hour (described in statistical reporting number 8413.70.2004)
8413.70.2004	Submersible centrifugal pumps, not fitted or designed to be fitted with a measuring device; other than fuel, lubricating or cooling medium pumps for internal combustion piston engines; other than stock pumps imported for use with machines for making cellulosic pulp, paper or paperboard; the foregoing rated not over 1.5 kW (described in statistical reporting number 8413.70.2004)
8413.70.2004	Tabletop water fountains designed for indoor use, the essential character of which is imparted by submersible centrifugal pumps (described in statistical reporting number 8413.70.2004)
8413.70.2005	Non-submersible centrifugal pumps for liquids (other than fuel, lubricating or cooling medium pumps for internal combustion piston engines), not fitted or designed to be fitted with a measuring device, the foregoing comprising single-stage, single-suction, close-coupled, with a discharge outlet under 5.08 cm in diameter, valued over \$4 but not over \$6.50 each (described in statistical reporting number 8413.70.2005)

8413.70.2015	Non-submersible centrifugal pumps for liquids (other than fuel, lubricating or cooling medium pumps for internal combustion piston engines), not fitted or designed to be fitted with a measuring device, the foregoing comprising single-stage, single-suction, close-coupled centrifugal motor pumps with a discharge outlet 5.08 cm or over in diameter, rated at 37 W or more but not exceeding 80 W and with a flow rate of 17 liters per minute or more (described in statistical reporting number 8413.70.2015)
8413.70.2022	Non-submersible centrifugal pumps for liquids (other than fuel, lubricating or cooling medium pumps for internal combustion piston engines), not fitted or designed to be fitted with a measuring device, the foregoing operating at a voltage of 120 V and a frequency of 60 Hz, valued over \$4 but not over \$9 each (described in statistical reporting number 8413.70.2022)
8413.70.2025	Non-submersible centrifugal pumps for liquids (other than fuel, lubricating or cooling medium pumps for internal combustion piston engines), not fitted or designed to be fitted with a measuring device, the foregoing comprising single-stage, single-suction, close-coupled, with discharge outlet under 5.08 cm in diameter each valued over \$150,000 (described in statistical reporting number 8413.70.2025)
8413.81.0040	Pet water drinking fountains, not incorporating centrifugal pumps (described in statistical reporting number 8413.81.0040)
8413.81.0040	Pumps (other than fuel, lubricating or cooling medium pumps for internal combustion piston engines, other than centrifugal pumps), not fitted or designed to be fitted with a measuring device, the foregoing rated at 37 W or more but not exceeding 80 W, with a flow rate of 17 liters or more per minute (described in statistical reporting number 8413.81.0040)
8413.91.9010	Tubes of copper alloy for use in solenoid fuel pumps, each valued not over \$1 (described in statistical reporting number 8413.91.9010)
8413.91.9095	Parts of pumps, other than fuel-injection pumps for compression-ignition engines or stock pumps imported for use with machines for making cellulosic pulp, paper or paperboard, the foregoing of plastics (described in statistical reporting number 8413.91.9095)
8413.91.9095	Rods and couplings designed for use with oil and gas field pumps, the foregoing of American Petroleum Institute grade (described in statistical reporting number 8413.91.9095)
8413.91.9095	Volutes of a kind designed for use with centrifugal sump pumps (described in statistical reporting number 8413.91.9095)
8414.30.4000	Air conditioner compressors of a kind used in motor vehicles (described in statistical reporting number 8414.30.4000)
8414.30.4000	Compressors designed for use in household refrigerators, not exceeding 187 W (1/4 horsepower), each valued not over \$30 (described in statistical reporting number 8414.30.4000)
8414.30.4000	Single phase, rotating piston type rotary compressors with split capacitor motors and refrigerant pumps, valued not over \$70 (described in statistical reporting number 8414.30.4000)
8414.30.8060	Rotary compressors, each exceeding 746 W (1 horsepower) but not exceeding 2,984 W (4 horsepower), with a cooling capacity ranging from 2,300 W (7,960 BTU) to 5,500 W (18,766 BTU) (described in statistical reporting number 8414.30.8060)

8414.30.8060	Rotary compressors, each exceeding 746 W (1 horsepower) but not exceeding 2,984 W (4 horsepower), with a cooling capacity ranging from 750 to 1400 W (described in statistical reporting number 8414.30.8060)
8414.30.8070	Scroll compressors, each exceeding 2,238 W (3 horsepower) but not exceeding 7,460 W (10 horsepower), valued over \$250 but not over \$500 each (described in statistical reporting number 8414.30.8070)
8414.30.8080	Scroll-type compressors, each exceeding 7,460 W (10 horsepower), valued over \$500 but not over \$900 (described in statistical reporting number 8414.30.8080)
8414.90.4165	Compressor housings designed for turbochargers (described in statistical reporting number 8414.90.4165)
8417.80.0000	Mineral slab production equipment including exhaust gas treatment apparatus therefor (described in statistical reporting number 8417.80.0000)
8417.80.0000	Twin reactor pyrolysis waste processing equipment consisting of two twin primary and one secondary processing units (described in statistical reporting number 8417.80.0000)
8417.90.0000	Parts of dry hearth melting furnaces (described in statistical reporting number 8417.90.0000)
8418.69.0110	Portable domestic ice cube makers of stainless steel, valued not over \$70 each (described in statistical reporting number 8418.69.0110)
8418.69.0160	Absorption liquid chilling units valued over \$130,000 each (described in statistical reporting number 8418.69.0160)
8418.69.0180	Chest-type coolers, compression type, with an interior volume exceeding 440 liters but not exceeding 600 liters (described in statistical reporting number 8418.69.0180)
8418.69.0180	Upright freezers, compression type, with an interior volume exceeding 1,300 liters but not exceeding 2,100 liters (described in statistical reporting number 8418.69.0180)
8419.50.1000	Brazed aluminum plate-fin heat exchangers, each valued not over \$250 (described in statistical reporting number 8419.50.1000)
8419.50.5000	Heat exchanger units, designed for use as part of a heat exchange system weighing more than 27 metric tons but not more than 32 metric tons and incorporating shell-and-tube type heat exchangers (described in statistical reporting number 8419.50.5000)
8419.50.5000	Heat exchanger units, designed for use as part of a heat exchange system weighing more than 40 but not more than 44 metric tons and designed to incorporate an ethylene dichloride vent eductor liquid cooler (described in statistical reporting number 8419.50.5000)
8419.50.5000	Heat exchanger units, designed for use as part of a heat exchange system weighing more than 63.5 metric tons and not designed to operate with chilled MCB Coolers using propylene refrigerant (described in statistical reporting number 8419.50.5000)
8419.50.5000	Heat exchanger units, designed for use individually or as part of a system weighing more than 63.5 metric tons and not designed to operate with chilled MCB coolers using propylene refrigerant (described in statistical reporting number 8419.50.5000)
8419.50.5000	Heat exchangers, each valued not over \$17,000 (described in statistical reporting number 8419.50.5000)
8419.50.5000	Industrial tubular heat exchange units (described in statistical reporting number 8419.50.5000)

8419.90.3000	Heat exchanger plates, cores, finned tubes, cones, shells, bonnets, flanges and baffles (described in statistical reporting number 8419.90.3000)
8420.10.9040	Calendering machines other than for metals or glass, such machines each weighing more than 12,000 kg (described in statistical reporting number 8420.10.9040)
8420.10.9040	Thermal roll laminators, each valued not over \$450 (described in statistical reporting number 8420.10.9040)
8420.99.9000	Cutting pads, platforms, base plates, pads, shims, trays, which function as guides for hand-operated table-top calendering machines of a width not exceeding 51 cm (described in statistical reporting number 8420.99.9000)
8421.21.0000	Glass water filtration pitchers and filters (described in statistical reporting number 8421.21.0000)
8421.21.0000	Household alkaline water ionizer and filtration apparatus (described in statistical reporting number 8421.21.0000)
8421.21.0000	Household water filter cartridges (described in statistical reporting number 8421.21.0000)
8421.21.0000	Ionization filters valued over \$35 but not over \$45 each (described in statistical reporting number 8421.21.0000)
8421.21.0000	Water filters for pet water fountains (described in statistical reporting number 8421.21.0000)
8421.29.0065	Accumulators for heat pumps and air conditioners, valued over \$8 but not over \$12 each (described in statistical reporting number 8421.29.0065)
8421.29.0065	Basket, Y-type or duplex strainers, each having a threaded or flanged-style end (described in statistical reporting number 8421.29.0065)
8421.29.0065	Cage-type cartridges, designed to remove water directly from fuel tanks, valued not over \$2 each (described in statistical reporting number 8421.29.0065)
8421.29.0065	Filtering or purifying machinery valued over \$2,500,000 (described in statistical reporting number 8421.29.0065)
8421.29.0065	Hydraulic fluid filters, rated at less than 100 kPa, measuring no more than 10 cm in diameter and 12 cm in length, each valued not more than \$2 (described in statistical reporting number 8421.29.0065)
8421.29.0065	Polymer filtration systems of a kind used to separate solid contaminants from liquid polymers, each valued over \$30,000 but not over \$40,000 (described in statistical reporting number 8421.29.0065)
8421.29.0065	Receiver-driers for air conditioning units used in commercial vehicles (described in statistical reporting number 8421.29.0065)
8421.29.0065	Stainless steel mesh filters with plastic cores, of a kind used for preventing clogs in paint sprayers, each valued not over \$1.50 (described in statistical reporting number 8421.29.0065)
8421.39.8090	Disposable plastic filters of a kind suitable for filtering and dehumidifying a patient's breath in a medical device such as a gas analyzer (described in statistical reporting number 8421.39.8090)
8421.99.0040	Fiberglass-reinforced polyethylene pressure vessels (described in statistical reporting number 8421.99.0040)
8421.99.0040	Parts of filters, each valued not over \$8 (described in statistical reporting number 8421.99.0040)
8421.99.0040	Parts of swimming pool vacuum cleaners (described in statistical reporting number 8421.99.0040)

8421.99.0040	Self-cleaning filters, of stainless steel, of a kind suitable for use in filtering municipal, agricultural or industrial water supplies, valued over \$700 but not over \$800 each (described in statistical reporting number 8421.99.0040)
8421.99.0040	Swimming pool filter cartridges (described in statistical reporting number 8421.99.0040)
8421.99.0080	Paint sprayer filters of paper, with steel mesh casings and plastic end caps, valued not over \$1 each (described in statistical reporting number 8421.99.0080)
8421.99.0080	Parts of vortex gas separators (described in statistical reporting number 8421.99.0080)
8422.30.9191	Vacuum sealing machines, each valued over \$30 but not over \$40 (described in statistical reporting number 8422.30.9191)
8422.90.0640	3-member slides with ball bearings, of stainless steel, for use in household dishwashers (described in statistical reporting number 8422.90.0640)
8422.90.0640	Stamped outer door panels of stainless steel for household dishwashing machines (described in statistical reporting number 8422.90.0640)
8423.20.1000	Electronic scales for continuous weighing of quartz, powder and resin on conveyors, capable of measuring 2 kg or more but not exceeding 100 kg of materials per minute (described in statistical reporting number 8423.20.1000)
8425.39.0100	Winches, each having a steel frame with a ratchet and pawl mechanism, operated manually (described in statistical reporting number 8425.39.0100)
8427.10.8010 prior to July 1, 2019	Electric operator-riding pallet trucks, each with a load capacity not exceeding 3,700 kg (described in statistical reporting number 8427.10.8010, prior to July 1, 2019 or described in 8427.10.8030, post July 1, 2019)
8427.10.8030 post July 1, 2019	Electric operator-riding pallet trucks, each with a load capacity not exceeding 3,700 kg (described in statistical reporting number 8427.10.8010, prior to July 1, 2019 or described in 8427.10.8030, post July 1, 2019)
8427.10.8010 prior to July 1, 2019	Electric operator-riding reach-type fork-lift trucks, each with a load capacity exceeding 1,300 kg but not exceeding 2,100 kg (described in statistical reporting number 8427.10.8010, prior to July 1, 2019 or described in statistical reporting number 8427.10.8030, post July 1, 2019)
8427.10.8030 post July 1, 2019	Electric operator-riding reach-type fork-lift trucks, each with a load capacity exceeding 1,300 kg but not exceeding 2,100 kg (described in statistical reporting number 8427.10.8010, prior to July 1, 2019 or described in statistical reporting number 8427.10.8030, post July 1, 2019)
8427.20.4000	Rider-type, counterbalanced fork-lift trucks, each powered by an internal combustion engine, with pneumatic tires, having a load capacity of 900 kg or more but not exceeding 18,000 kg (described in statistical reporting number 8427.20.4000)
8427.20.4000	Rider-type, counterbalanced fork-lift trucks, each powered by an internal combustion engine, with solid tires, having a load capacity of 1,300 kg or more but not exceeding 3,000 kg (described in statistical reporting number 8427.20.4000)
8431.39.0010	Baggage carriers, of polyethylene, suitable for use solely or principally with conveyors of subheading 8428.39 (described in statistical reporting number 8431.39.0010)
8428.39.0000	Continuous action elevators and conveyors of the kind designed for use in airports for handling baggage (described in statistical reporting number 8428.39.0000)
8428.39.0000	Roller conveyors with pallet rotators or pallet corner rotators (described in statistical reporting number 8428.39.0000)

8428.90.0290	Rotary positioning machines for use with machine tools (described in statistical reporting number 8428.90.0290)
8429.51.1055	Shovel loaders, each with a bucket capacity of 11.4 m ³ to 12 m ³ , and an operating weight of 30,000 kg or more but not exceeding 36,000 kg (described in statistical reporting number 8429.51.1055)
8431.10.0090	Winch handles (described in statistical reporting number 8431.10.0090)
8431.20.0000	Parts suitable for use solely or principally with self-propelled works trucks powered by an electric motor and fitted with lifting or handling equipment of subheading 8427.10 (described in statistical reporting number 8431.20.0000)
8431.39.0010	Drive frames weighing over 3.6 metric tons and parts thereof (described in statistical reporting number 8431.39.0010)
8431.41.0040	Grappler attachments, other than buckets, each valued over \$250 but not over \$350 (described in statistical reporting number 8431.41.0040)
8431.41.0040	Grappler buckets, each valued over \$800 but not over \$900 (described in statistical reporting number 8431.41.0040)
8431.43.8060	Bridge plug assemblies for oil and gas boring or sinking machinery, other than for offshore oil and natural gas drilling and production platforms (described in statistical reporting number 8431.43.8060)
8431.49.9020	Metal frames or assemblies of a kind suitable for use as attachments to agricultural tractors (described in statistical reporting number 8431.49.9020)
8431.49.9095	Counterweight castings of iron or steel designed for use on excavators and wheel loaders (described in statistical reporting number 8431.49.9095)
8431.20.0000	Counterweight castings of iron or steel, designed for use on skid loaders (described in statistical reporting number 8431.20.0000)
8431.49.9095	Dredge cutter teeth, comprising parts suitable for use solely or principally with the machinery of heading 8429 or 8430 (described in statistical reporting number 8431.49.9095)
8432.90.0050	Parts of harrows or cultivators incorporating bearings (described in statistical reporting number 8432.90.0050)
8432.90.0060	Ductile iron casting, weighing more than 0.75 kg but not more than 18.25 kg, with a maximum dimension exceeding 190 mm but not exceeding 695 mm (described in statistical reporting number 8432.90.0060)
8436.10.0000	Electrically powered granulator machine (described in statistical reporting number 8436.10.0000)
8436.80.0090	Animal feeding machinery (described in statistical reporting number 8436.80.0090)
8436.99.0090	Parts of animal feeding machinery (described in statistical reporting number 8436.99.0090)
8441.40.0000	Machines, of a kind used to produce cylindrical paper drinking straws (described in statistical reporting number 8441.40.0000)
8443.99.2010	Ink cartridges, each weighing more than 1 kg (described in statistical reporting number 8443.99.2010)
8443.99.2050	Paper handling assemblies as described in Additional U.S. note 2(g) to chapter 84 (described in statistical reporting number 8443.99.2050)
8443.99.2050	Printer maintenance kits consisting of two or more replacement parts for printer units of subheading 8443.32.10 specified in additional U.S. note 2 to chapter 84 (described in statistical reporting number 8443.99.2050)

8454.30.0010	Cold-chamber die casting machines having a maximum casting volume of 52.78 m ³ , a die height of 0.4 m or more but not exceeding 1 m, and a maximum die locking force of 8,400 kN (described in statistical reporting number 8454.30.0010)
8455.90.8000	Cylindrical side guides, the foregoing comprising parts of metal-rolling mills (described in statistical reporting number 8455.90.8000)
8458.19.0020	Horizontal lathes for removing metal, electrically powered, not numerically controlled, each with mill head attachment mounted above the lathe headstock (described in statistical reporting number 8458.19.0020)
8459.10.0000	Way-type unit head machine tools, each valued over \$1,800 but not over \$2,200 (described in statistical reporting number 8459.10.0000)
8459.61.0080	New numerically-controlled milling machines capable of end beveling pipe of an outside diameter of 60 cm or more but not exceeding 305 cm (described in statistical reporting number 8459.61.0080)
8459.69.0020	Benchtop milling machines, not numerically controlled, valued over \$400 but not over \$700 each (described in statistical reporting number 8459.69.0020)
8462.29.0030	Press brakes, not numerically controlled, having a drive capacity rating of 3kW (described in statistical reporting number 8462.29.0030)
8462.39.0050	New hydraulic shearing machines, not numerically controlled, with a power of 7.5 kW, valued at \$3,025 or more each (described in statistical reporting number 8462.39.0050)
8462.91.8090	Hydraulic presses, not numerically controlled, each valued over \$85,000 but not over \$110,000 (described in statistical reporting number 8462.91.8090)
8462.91.8090	Machines for end-forming metal pipes, such pipes ranging in outside diameter from 60 cm or more but not exceeding 305 cm (described in statistical reporting number 8462.91.8090)
8465.92.0051	Woodworking routers, each with a 1,306 W (1-3/4 horsepower) motor and valued not over \$60 (described in statistical reporting number 8465.92.0051)
8465.99.0220	Woodworking lathes, each with a motor of 224 watts (0.3 horsepower) or more but not exceeding 896 W (1.2 horsepower), the foregoing which operate at speeds of 600 to 3,500 rpm, valued not over \$130 each (described in statistical reporting number 8465.99.0220)
8466.10.0175	Tool holders of a kind used to hold various types of metal working tools for use on milling machine spindles (described in statistical reporting number 8466.10.0175)
8466.30.8000	Machine tool stands having leveling, stabilizing, attachment or other special features (described in statistical reporting number 8466.30.8000)
8466.92.5010	Work stands designed for use with miter saws, whether or not wheeled (described in statistical reporting number 8466.92.5010)
8467.11.1040	Rotary grinders for working in the hand, suitable for metal working, each valued under \$10 (described in statistical reporting number 8467.11.1040)
8467.11.1040	Rotary sanders for working in the hand, suitable for metal working, each valued under \$20 (described in statistical reporting number 8467.11.1040)
8467.11.1080	Pneumatic rotary cutters, suitable for metal working, each with a maximum blade diameter of 11 cm and a maximum speed of 20,000 rpm, valued under \$10 each (described in statistical reporting number 8467.11.1080)
8471.70.9000	External optical disk drive storage units enclosed in cases, each valued under \$60 (described in statistical reporting number 8471.70.9000)

8473.40.8600	Parts of automatic teller machines (described in statistical reporting number 8473.40.8600)
8474.10.0090	Stationary sand screening equipment having more than 90 but less than 182 metric ton per hour capacity (described in statistical reporting number 8474.10.0090)
8474.31.0000	Portable concrete or mortar mixers, electrically powered, with a capacity not exceeding 0.15 m3 (described in statistical reporting number 8474.31.0000)
8474.80.0015	Mineral pressing machine equipped with vibration motors (described in statistical reporting number 8474.80.0015)
8477.80.0000	Electrically powered cutting machines for working supple plastics, valued not over \$300 per unit (described in statistical reporting number 8477.80.0000)
8477.90.8501	Injection mold inserts (described in statistical reporting number 8477.90.8501)
8477.90.8501	Mold base parts, each with a length of more than 19 cm but not more than 91 cm, a width of more than 3 cm but not more than 61 cm and a thickness of more than 2 cm but not more than 16 cm; the foregoing preconfigured with standard mill features such as drilled holes, slots and bushings to accommodate the various pins and tube dowels necessary for the functioning of the plastic injection mold (described in statistical reporting number 8477.90.8501)
8477.90.8540	Sidewall plates, top bead rings, bottom bead rings and upper bag clamp rings, of steel, all the foregoing being parts of tire molds (described in statistical reporting number 8477.90.8540)
8479.82.0040	Machines of a kind suitable for mixing granules of rock or similar hard materials with plastic resin to form a homogenous mixture (described in statistical reporting number 8479.82.0040)
8479.82.0040	Modularized plants for the manufacture of lithium hydroxide by functions involving mixing, kneading or stirring (described in statistical reporting number 8479.82.0040)
8479.82.0080	Machines for crushing/grinding pills, each valued over \$20 but not over \$35 (described in statistical reporting number 8479.82.0080)
8479.89.9499	Granulating machines not specifically designated for use with specific particulate materials, each valued more than \$25,000 (described in statistical reporting number 8479.89.9499)
8479.89.9499	Vertical or single shaft shredding machines of a kind suitable for use in the recycling industry, weighing over 10,000 kg but not over 15,000 kg each (described in statistical reporting number 8479.89.9499)
8479.90.9496	Parts of drain and sewer cleaning machines (described in statistical reporting number 8479.90.9496)
8479.90.9496	Parts of suspension arms of a kind used in dental lighting or delivery systems (described in statistical reporting number 8479.90.9496)
8480.20.0000	Mold bases, of steel, measuring 27.9 cm by 38.1 cm by 45.7 cm, each weighing 409.1 kg (described in statistical reporting number 8480.20.0000)
8480.30.0000	Plastic injection molding patterns each valued over \$50,000 (described in statistical reporting number 8480.30.0000)
8480.71.8060	Compression type tire molds (described in statistical reporting number 8480.71.8060)
8481.20.0020	Hydraulic solenoid timing valve each valued not over \$20 (described in statistical reporting number 8481.20.0020)
8481.30.9000	Check valves, of plastics or rubber (described in statistical reporting number 8481.30.9000)

8481.90.9020	Ball type angle cock valve bodies, of cast iron, for oleohydraulic or pneumatic transmissions (described in statistical reporting number 8481.90.9020)
8481.90.9020	Valve bodies, of aluminum, of valves for oleohydraulic or pneumatic transmissions (described in statistical reporting number 8481.90.9020)
8481.90.9040	Hydraulic valve parts, other than valve bodies, of valves for oleohydraulic or pneumatic transmissions, each valued not over \$5 (described in statistical reporting number 8481.90.9040)
8481.90.9085	Valve pressure relief components, including body covers, and diaphragms (described in statistical reporting number 8481.90.9085)
8482.10.5004	Unground ball bearings each valued not over \$4 (described in statistical reporting number 8482.10.5004)
8482.10.5008	Thrust bearings each valued not over \$2 (described in statistical reporting number 8482.10.5008)
8482.10.5016	Wheel hub bearing units, of steel, of a kind used on motor vehicles, trailers and lawn equipment, each having one flange for the wheel and brake attachment and a second flange for attaching to the vehicle suspension, and having a sealed and lubricated double row of bearings (described in statistical reporting number 8482.10.5016)
8482.10.5028	Angular contact ball bearings, not for use with wheel hub bearing units, having an inner diameter of 25 mm or greater but not exceeding 55 mm, an outer diameter of 50 mm or greater but not exceeding 95 mm, a width of 20 mm or greater but not exceeding 35 mm, with single or double row of steel balls and a cage of steel or plastics (described in statistical reporting number 8482.10.5028)
8482.10.5028	Angular contact ball bearings, not over 40 mm in width, other than wheel hub bearing units (described in statistical reporting number 8482.10.5028)
8482.10.5028	Single row angular contact ball bearings, other than wheel hub bearing units, valued over \$5.50 but not over \$6.25 each (described in statistical reporting number 8482.10.5028)
8482.10.5036	Single row radial bearings, with an outside diameter less than 9 mm, each valued not over \$1 (described in statistical reporting number 8482.10.5036)
8482.10.5056	Single row radial bearings, with an outside diameter over 100 mm, each valued not over \$9 (described in statistical reporting number 8482.10.5056)
8482.10.5060	Radial double row ball bearings, having an inner diameter of 10 mm or greater but not exceeding 90 mm, an outside diameter of 30 mm or greater but not exceeding 170 mm, and a width of 14.3 mm or greater but not exceeding 68.3 mm, with a cage of steel or plastics (described in statistical reporting number 8482.10.5060)
8482.20.0061	Tapered roller bearings, with cups having an outside diameter exceeding 102 mm but not exceeding 203 mm, each valued not over \$9 (described in statistical reporting number 8482.20.0061)
8482.20.0070	Single row tapered roller bearing cone assemblies for cups having an outside diameter not exceeding 102 mm (described in statistical reporting number 8482.20.0070)
8482.20.0081	Steel tapered roller bearing cone assemblies, entered without cups, with an inner race that extends beyond the width of the roller cage, for cups having an outside diameter exceeding 102 mm but not exceeding 203 mm (described in statistical reporting number 8482.20.0081)

8482.20.0081	Tapered roller bearing cone assemblies, each valued not over \$9, for cups having an outside diameter exceeding 102 mm but not exceeding 203 mm (described in statistical reporting number 8482.20.0081)
8482.20.0090	Single row tapered roller bearing cone assemblies for cups having an outside diameter exceeding 203 mm (described in statistical reporting number 8482.20.0090)
8482.30.0080	Spherical roller bearings, other than single row, with an inside diameter of 20 mm or greater but not exceeding 300 mm, an outside diameter of 50 or greater but not exceeding 300 mm, and a width of 15 mm or greater but not exceeding 100 mm (described in statistical reporting number 8482.30.0080)
8482.50.0000	Cylindrical roller thrust bearings, each having an inside diameter of 77.2 mm, an outer diameter of 95.6 mm, and a width of 3.445 mm, comprising 64 cylindrical rollers measuring 2.24 mm in diameter and 5 mm in length, a steel cage and a steel axial washer (described in statistical reporting number 8482.50.0000)
8482.99.6510	Adapter sleeve assemblies for spherical roller bearings consisting of a tapered sleeve adapter, a locknut and lock washer (described in statistical reporting number 8482.99.6510)
8483.50.6000	Flywheels of a kind used in manual automotive transmission (described in statistical reporting number 8483.50.6000)
8483.60.4080	Universal joints, each weighing not more than 5 kg (described in statistical reporting number 8483.60.4080)
8483.90.1010	Chain sprockets with forged hubs, the foregoing with outer diameter of 59.4 mm or greater but not exceeding 999.4 mm and width of 22.4 mm or greater but not exceeding 114.3 mm (described in statistical reporting number 8483.90.1010)
8483.90.1050	Chain sprockets, each not more than 55 mm in diameter (described in statistical reporting number 8483.90.1050)
8484.10.0000	Gaskets of metal sheeting combined with other material or of two or more layers of metal, each of the foregoing valued not over \$3 (described in statistical reporting number 8484.10.0000)
8487.90.0080	Machinery parts, not containing electrical connectors, insulators, coils, contacts or other electrical features, and not specified or included elsewhere in chapter 84, each valued not over \$20 (described in statistical reporting number 8487.90.0080)
8501.10.4020	AC motors, C-frame single-phase induction-type, without external housing, of an output not exceeding 18.65 W, not synchronous, each valued not over \$20 (described in statistical reporting number 8501.10.4020)
8501.10.4020	Electric motors, AC, permanent split capacitor type, not exceeding 16 W (described in statistical reporting number 8501.10.4020)
8501.10.4020	Electric motors, AC, permanent split capacitor type, with a height of 97.5 mm or more but not exceeding 127.0 mm and a length of 82.8 mm or more but not exceeding 226.0 mm, with an output of 8.9 kW or more but not exceeding 12 kW, 60 hertz (described in statistical reporting number 8501.10.4020)
8501.10.4020	Shaded-pole AC motors, of an output not exceeding 18.65 W, each valued not over \$5 (described in statistical reporting number 8501.10.4020)
8501.10.4040	Brushless motors, of an output not exceeding 18.65 W, not synchronous, each valued not over \$0.50 (described in statistical reporting number 8501.10.4040)
8501.10.4060	DC servo motors or actuators, of an output of under 18.65 W, valued over \$2 but not over \$2.50 each (described in statistical reporting number 8501.10.4060)

8501.20.2000	Universal AC/DC motors, each rated at more than 37.5 W but not more than 65 W and valued at less than \$20 (described in statistical reporting number 8501.20.2000)
8501.20.6000	Quarter-turn actuator motors, of an output exceeding 746 W, each valued not over \$140 (described in statistical reporting number 8501.20.6000)
8501.31.2000	DC motors, brushless, of an output rated at 48 W or greater but not exceeding 60 W, each valued not over \$14 (described in statistical reporting number 8501.31.2000)
8501.31.2000	DC motors, brushless, rated at 32 V, designed to operate in saltwater environment, each valued over \$35 (described in statistical reporting number 8501.31.2000)
8501.31.2000	DC motors, of an output exceeding 37.5 W but not exceeding 74.6 W, each incorporating a thermal switch, the foregoing valued not over \$22 (described in statistical reporting number 8501.31.2000)
8501.31.2000	DC motors, of an output exceeding 37.5 W but not exceeding 74.6 W, valued over \$2 but not over \$30 each (described in statistical reporting number 8501.31.2000)
8501.51.4040	AC motors, multiphase, of a kind used with paint sprayers to regulate the flow of paint, of an output exceeding 74.6 W but not exceeding 735 W, valued not over \$200 each (described in statistical reporting number 8501.51.4040)
8501.31.6000	Brushless, variable speed, DC motors, of an output of 750 W (described in statistical reporting number 8501.31.6000)
8501.31.6000	DC motor and gear box assemblies, of an output of 746 W or more but not exceeding 750W, of a kind used to open and close a swing door, the foregoing valued not over \$300 each (described in statistical reporting number 8501.31.6000)
8501.51.2040	AC motors, multi-phase, of an output exceeding 37.5 W but not exceeding 74.6 W, other than gear motors, each weighing less than 600 grams and valued less than \$15 (described in statistical reporting number 8501.51.2040)
8501.51.4040	AC motors, multi-phase, of an output exceeding 37.5 W but not exceeding 74.6 W, each fitted with a timing belt (described in statistical reporting number 8501.51.4040)
8501.51.4040	AC motors, multi-phase, of rolled steel frame construction (described in statistical reporting number 8501.51.4040)
8501.52.8040	AC motors, multiphase, of an output exceeding 74 kW but not exceeding 75 kW, other than for use in civil aircraft (described in statistical reporting number 8501.52.8040)
8501.53.4080	AC motors, multi-phase, of an output exceeding 93 kW but not exceeding 112 kW (described in statistical reporting number 8501.53.4080)
8501.53.8040	AC motors, multi-phase, of an output of 186.5 kW or more but not exceeding 373 kW, having a cast iron frame construction (described in statistical reporting number 8501.53.8040)
8501.63.0000	AC generators, each having copper windings and weighing more than 900 kg but not more than 1700 kg (described in statistical reporting number 8501.63.0000)
8501.64.0025	AC generators, of an output exceeding 750 kVA but not exceeding 10,000 kVA, each having copper windings and weighing more than 1650 kg but not more than 4100 kg, other than for wind-powered generating sets classified within 8502.31.00 (described in statistical reporting number 8501.64.0025)
8502.11.0000	Generator sets each weighing more than 650 kg but not over 830 kg (described in statistical reporting number 8502.11.0000)
8503.00.6500	Armatures, other than for motors of under 18.65 W, other than for generators for civil aircraft, each valued not over \$5 (described in statistical reporting number 8503.00.6500)

8503.00.6500	Motor field cores, other than for motors of under 18.65 W, other than for generators for civil aircraft, of steel stamping, each valued not over \$5 (described in statistical reporting number 8503.00.6500)
8503.00.6500	Stators and rotors designed for use with household laundry washing machines or tabletop household appliances, each valued not over \$10 (described in statistical reporting number 8503.00.6500)
8503.00.6500	Stators and rotors, 2 or 4 pole type, valued over \$4,700 but not over \$4,900 each (described in statistical reporting number 8503.00.6500)
8504.32.0000	Electrical transformers, each weighing not over 500 grams (described in statistical reporting number 8504.32.0000)
8504.90.6500	Printed circuit boards, each measuring no more than 2.3 cm by 13.1 cm, presented with two black plastic pin connectors on opposite ends and/or sides, designed for use in transformers used to provide power to telecommunications networks (described in statistical reporting number 8504.90.6500)
8504.90.7500	Dual layer printed circuit board assemblies, each valued over \$30 but not over \$35 (described in statistical reporting number 8504.90.7500)
8504.90.9646	Coils for cast epoxy resin transformers, each of the foregoing valued over \$6,500 but not over \$7,000 (described in statistical reporting number 8504.90.9646)
8504.90.9690	Conductors of aluminum for electric transformers, static converters and inductors (described in statistical reporting number 8504.90.9690)
8504.90.9690	Heat sinks of aluminum for electric transformers, static converters and inductors (described in statistical reporting number 8504.90.9690)
8504.90.9690	Inductor parts, of plastics (described in statistical reporting number 8504.90.9690)
8504.90.9690	Toroids of silicon steel (described in statistical reporting number 8504.90.9690)
8506.50.0000	Lithium primary batteries valued over \$0.50 but not over \$0.75 each (described in statistical reporting number 8506.50.0000)
8514.10.0000	Resistance-heated annealing ovens (described in statistical reporting number 8514.10.0000)
8514.10.0000	Resistance-heated glass furnaces, each with continuous conveyance articulating roller and positive press (described in statistical reporting number 8514.10.0000)
8514.40.0000	Resistance-heated strip casting furnaces (described in statistical reporting number 8514.40.0000)
8515.11.0000	Manually operated soldering irons and guns, with or without their power supplies but without work stands or other accessory devices (described in statistical reporting number 8515.11.0000)
8515.90.2000	Tungsten electrodes for tungsten inert gas arc welding torches (described in statistical reporting number 8515.90.2000)
8525.60.1050	Transceivers, 10-meter, not hand-held, for operation in infrequencies of 28.000 to 29.700 MHz (described in statistical reporting number 8525.60.1050)
8526.91.0040	GPS apparatus measuring not over 118 mm in height, 120 mm in width and 20 mm in thickness, presented with or without attached antenna or other accessories (described in statistical reporting number 8526.91.0040)
8526.91.0040	GPS apparatus suitable for use with dog or other animal collars (described in statistical reporting number 8526.91.0040)

8526.91.0040	Kits each consisting of GPS apparatus suitable for use with dog or animal collars, a hand-held GPS transmitter and accessories therefor (described in statistical reporting number 8526.91.0040)
8526.92.5000	Radio remote control apparatus of a kind suitable for controlling gas burning fireplaces (described in statistical reporting number 8526.92.5000)
8529.10.4040	27 MHz radio remote control antennas each of a kind designed to transmit a signal to a dog collar receiver (described in statistical reporting number 8529.10.4040)
8529.10.9100	CB radio antennas (described in statistical reporting number 8529.10.9100)
8532.22.0055	Aluminum electrolytic capacitors each valued not over \$1.50 (described in statistical reporting number 8532.22.0055)
8532.24.0020	Fixed ceramic dielectric multilayer chip capacitors, each valued not over \$0.12 per unit (described in statistical reporting number 8532.24.0020)
8532.25.0010	Dielectric capacitors of paper or plastics, for AC service, operating at less than 300 V each valued not over \$4.50 (described in statistical reporting number 8532.25.0010)
8532.25.0020	Dielectric capacitors of paper or plastics, for AC service, operating at 300 V or more but not exceeding 600 V, each valued not over \$3 (described in statistical reporting number 8532.25.0020)
8532.25.0080	Double-sided capacitor modules, each containing capacitors operating at 165 farad, 48 V, and 53 watt-hours (described in statistical reporting number 8532.25.0080)
8532.29.0040	Fixed capacitors (the foregoing other than tantalum, aluminum electrolytic, ceramic dielectric, dielectrics of paper or plastics or mica dielectric), each valued over \$200 but not over \$300 (described in statistical reporting number 8532.29.0040)
8532.30.0090	Variable capacitors (other than mica, ceramic or glass dielectric), each valued over \$500 but not over \$600 (described in statistical reporting number 8532.30.0090)
8533.40.4000	Metal oxide varistors of ceramic metal oxide materials (described in statistical reporting number 8533.40.4000)
8533.40.8070	Potentiometers (other than cermet or metal glaze), each valued not over \$70 (described in statistical reporting number 8533.40.8070)
8533.40.8070	Thermistors (other than cermet or metal glaze), each valued not over \$1 (described in statistical reporting number 8533.40.8070)
8536.30.4000	Motor overload protectors for a voltage exceeding 60 V but not exceeding 1,000 V, each valued over \$5 but not over \$7 (described in statistical reporting number 8536.30.4000)
8536.49.0065	Contactors for a voltage not exceeding 1,000 V, each valued not over \$18 (described in statistical reporting number 8536.49.0065)
8536.50.4000	Motor starters for a voltage exceeding 60 V but not exceeding 1,000 V, valued over \$9 but not over \$10 each (described in statistical reporting number 8536.50.4000)
8536.50.9020	Rotary switch assemblies, for a voltage not exceeding 1,000 V, rated at not over 5 A, each valued over \$2 but not over \$3 (described in statistical reporting number 8536.50.9020)
8536.50.9040	Snap-action switches, for a voltage not exceeding 250 V, rated not over 8 A (described in statistical reporting number 8536.50.9040)
8536.50.9055	Limit switches, for a voltage not exceeding 1,000 V, each valued over \$19 but not over \$32 (described in statistical reporting number 8536.50.9055)
8536.50.9065	Broken belt switches, for a voltage not exceeding 1,000 V, designed for use in clothes dryers (described in statistical reporting number 8536.50.9065)

8536.50.9065	Modular light switches, for a voltage not exceeding 1,000 V, presented in polyethylene terephthalate (PET) housings, designed for use with a backplate (described in statistical reporting number 8536.50.9065)
8536.50.9065	Single-pole, double-throw switches, for a voltage not exceeding 100 V, each with a movable contact arm permitting the opening and closing of contact points (described in statistical reporting number 8536.50.9065)
8536.50.9065	Switches designed for use in motor vehicles, driver or passenger activated (described in statistical reporting number 8536.50.9065)
8536.69.4010	Coaxial connectors, for a voltage not exceeding 1,000 V, valued over \$0.20 but not over \$0.30 each (described in statistical reporting number 8536.69.4010)
8536.69.4020	Cylindrical multicontact connectors, for a voltage not exceeding 1,000 V, each valued not over \$120 (described in statistical reporting number 8536.69.4020)
8536.69.4040	Printed circuit connectors each valued not over \$1 (described in statistical reporting number 8536.69.4040)
8536.69.4040	Printed circuit connectors, for a voltage not exceeding 1,000 V, measuring 142 mm long, 20.53 mm high and 6.5 mm wide (described in statistical reporting number 8536.69.4040)
8536.69.4040	Printed circuit connectors, for a voltage not exceeding 1,000 V, measuring 59.08 mm long, 25.91 mm high and 25.91 mm wide, each valued not over \$20 (described in statistical reporting number 8536.69.4040)
8536.69.4040	Printed circuit connectors, for a voltage not exceeding 1,000 V, each valued over \$1 but not over \$5 (described in statistical reporting number 8536.69.4040)
8536.69.4040	Printed circuit connectors, for a voltage not exceeding 1,000 V, stacked, each valued not over \$10 (described in statistical reporting number 8536.69.4040)
8536.90.4000	Butt splice connectors, for a voltage not exceeding 1,000 V, each valued not over \$3 (described in statistical reporting number 8536.90.4000)
8536.90.4000	Kits each containing 40 assorted terminals comprising 12 butt splices, 10 ring terminals, 8 spade terminals and 10 female disconnects, for a voltage not exceeding 1,000 V (described in statistical reporting number 8536.90.4000)
8536.90.4000	Kits each containing 80 assorted terminals, valued not over \$2, for a voltage not exceeding 1,000 V (described in statistical reporting number 8536.90.4000)
8536.90.4000	Ring terminals, for a voltage not exceeding 1,000 V (described in statistical reporting number 8536.90.4000)
8536.90.4000	Twist-on wire connectors, for a voltage not exceeding 1,000 V, each valued not over \$0.03 (described in statistical reporting number 8536.90.4000)
8536.90.8530	Junction boxes, each valued over \$1.40 but not over \$1.70 (described in statistical reporting number 8536.90.8530)
8541.21.0075	Transistors, with a dissipation rate of less than 1 W and an operating frequency of not less than 100 MHz, valued over \$0.04 but not over \$0.05 each (described in statistical reporting number 8541.21.0075)
8541.21.0095	Bipolar junction transistors, with a dissipation rate of less than 1 W and with an operating frequency of less than 100 MHz (described in statistical reporting number 8541.21.0095)
8541.29.0095	Metal-oxide transistors on a silicon-carbide substrate, with a dissipation rate of less than 1 W and an operating frequency of less than 100 MHz (described in statistical reporting number 8541.29.0095)

8541.60.0060	Mounted quartz piezoelectric crystals operating at a supply voltage of 1.5 V or greater but not exceeding 3.75 V and a frequency range not over 175 MHz (described in statistical reporting number 8541.60.0060)
8543.10.0000	S-band and X-band linear accelerators designed for use in radiation surgery or radiation therapy equipment (described in statistical reporting number 8543.10.0000)
8543.30.2000	Copper panel or pattern electroplating machines of a kind used solely or principally for the manufacture of printed circuits (described in statistical reporting number 8543.30.2000)
8543.30.2000	Electrolysis copper etchback and desmear machines of a kind used solely or principally for the manufacture of printed circuits (described in statistical reporting number 8543.30.2000)
8544.30.0000	Coaxial antenna feeder cables designed for use in motor vehicles (described in statistical reporting number 8544.30.0000)
8544.30.0000	Ignition coil and wiring sets designed for use with motor vehicle engines, each valued not over \$7 (described in statistical reporting number 8544.30.0000)
8544.30.0000	Power supply cables designed for use in aircraft (described in statistical reporting number 8544.30.0000)
8544.30.0000	Wiring sets designed for use with motor vehicle gear shifters, each valued not over \$7 (described in statistical reporting number 8544.30.0000)
8544.49.9000	Insulated aluminum cables, not fitted with connectors, for a voltage exceeding 80 V but not exceeding 600 V (described in statistical reporting number 8544.49.9000)
8703.21.0110	Four-wheel off-road vehicles, with only spark-ignition internal combustion reciprocating piston engines, of a cylinder capacity not exceeding 1,000 cc, with straddle seat and handlebar control, each with label indicating that vehicle is for operation only by persons at least 16 years of age, each valued not over \$5000 (described in statistical reporting number 8703.21.0110)
8709.11.0030	Works trucks, electrical, operator riding, each of a curb weight exceeding 8,500 kg but not exceeding 9,500 kg (described in statistical reporting number 8709.11.0030)
8803.30.0030	Gearhead assemblies, and parts thereof, for use in civil aircraft, each valued not over \$40 (described in statistical reporting number 8803.30.0030)
8803.90.9060	Wing, tail, fuselage and other body sections, including structural components and parts of the foregoing, designed for use on drone aircraft not capable of transporting persons (described in statistical reporting number 8803.90.9060)
9002.90.9500	Motor vehicle lens cover assemblies (described in statistical reporting number 9002.90.9500)
9011.90.0000	Accessories designed for compound optical microscope stages (described in statistical reporting number 9011.90.0000)
9011.90.0000	Camera adapter mounts designed for compound optical microscopes (described in statistical reporting number 9011.90.0000)
9011.90.0000	Episcopic fluorescence microscopy accessories designed for compound optical microscopes (described in statistical reporting number 9011.90.0000)
9013.20.0000	Lasers, other than laser diodes, each valued over \$200 but not over \$300 (described in statistical reporting number 9013.20.0000)
9013.80.7000	Liquid-crystal displays, each measuring not over 85 cm in diagonal measurement (described in statistical reporting number 9013.80.7000)

9014.80.2000	Depth-sounding apparatus, each valued not over \$50 (described in statistical reporting number 9014.80.2000)
9014.90.6000	Parts, of plastics, of fish finders of subheading 9014.80.20 (described in statistical reporting number 9014.90.6000)
9018.11.9000	Disposable electrocardiograph (ECG) electrodes (described in statistical reporting number 9018.11.9000)
9018.12.0000	Portable ultrasonic scanner consoles, each weighing less than 4 kg, presented with or without transducer (described in statistical reporting number 9018.12.0000)
9018.19.9550	Digital peak flow meters suitable for use by medical professionals (described in statistical reporting number 9018.19.9550)
9018.19.9550	Fingertip pulse oximeters suitable for use by medical professionals (described in statistical reporting number 9018.19.9550)
9018.19.9560	Bismuth germanate crystals with set dimensional and surface finish requirements and used as a detection element in Positron Emission Tomography (PET) detectors (described in statistical reporting number 9018.19.9560)
9018.19.9560	Magnetic resonance imaging ("MRI") patient enclosure devices, each incorporating radio frequency and gradient coils (described in statistical reporting number 9018.19.9560)
9018.19.9560	Parts and accessories of capnography monitors (described in statistical reporting number 9018.19.9560)
9018.90.2000	Otoscopes (described in statistical reporting number 9018.90.2000)
9018.90.3000	Anesthesia masks (described in statistical reporting number 9018.90.3000)
9018.90.6000	Electrosurgical cautery pencils with electrical connectors (described in statistical reporting number 9018.90.6000)
9018.90.7580	Printed circuit board assemblies designed for use in displaying operational performance of medical infusion equipment (described in statistical reporting number 9018.90.7580)
9022.90.2500	X-ray tables (described in statistical reporting number 9022.90.2500)
9022.90.4000	X-ray tube housings and parts thereof (described in statistical reporting number 9022.90.4000)
9022.90.6000	Parts and accessories, of metal, for mobile X-ray apparatus (described in statistical reporting number 9022.90.6000)
9022.90.6000	Printed circuit board assemblies, of a kind designed for use in X-ray apparatus (described in statistical reporting number 9022.90.6000)
9022.90.6000	Tungsten shielding, containing 90% or more of tungsten, of a kind designed to be attached to the walls of the multileaf collimator of the specific radiotherapy apparatus based on the use of X-rays (described in statistical reporting number 9022.90.6000)
9022.90.6000	Vertical stands specially designed to support, contain or adjust the movement of X-ray digital detectors, or the X-ray tube and collimator in complete X-ray diagnostic systems (described in statistical reporting number 9022.90.6000)
9022.90.9500	Thermoplastic masks for radiation therapy, affixed to the treatment table when used, each valued over \$18 but not over \$23 (described in statistical reporting number 9022.90.9500)
9026.10.2040	Electromagnetic flow meter systems for pipes with outside diameters larger than 183 cm (described in statistical reporting number 9026.10.2040)

9026.20.4000	Digital tire pressure gauges, each valued not over \$2 (described in statistical reporting number 9026.20.4000)
9027.90.5910	Carbon monoxide sensors, each having a value exceeding \$14 but not exceeding \$19 (described in statistical reporting number 9027.90.5910)
9027.90.5910	Hydrogen sulfide sensors, each having a value exceeding \$9 but not exceeding \$13 (described in statistical reporting number 9027.90.5910)
9027.90.5910	Nitrogen dioxide sensors, each having a value exceeding \$12 but not exceeding \$17 (described in statistical reporting number 9027.90.5910)
9027.90.5910	Sulfur dioxide sensors, each having a value exceeding \$24 but not exceeding \$29 (described in statistical reporting number 9027.90.5910)
9027.90.5995	Microtome universal cassette clamps (described in statistical reporting number 9027.90.5995)
9028.90.0040	Utility meter bases, of plastics, each 17 cm or greater but not exceeding 18 in diameter, incorporating a latching relay, the foregoing valued over \$8 but not over \$10 (described in statistical reporting number 9028.90.0040)
9030.40.0000	Waveform monitors, each valued over \$4,000 but not over \$5,000 (described in statistical reporting number 9030.40.0000)
9030.90.2500	Printed circuit board assemblies designed for use with X-ray detectors (described in statistical reporting number 9030.90.2500)
9030.90.8911	Oscilloscope probes (described in statistical reporting number 9030.90.8911)
9032.10.0030	Automatic thermostats for heating, ventilation and air conditioning systems, containing temperature and humidity sensors, designed for wall mounting (described in statistical reporting number 9032.10.0030)
9032.10.0060	Thermostats for air conditioning, refrigeration or heating systems, designed for use in motor vehicles (described in statistical reporting number 9032.10.0060)
9032.10.0060	Thermostats for air conditioning, refrigeration or heating systems, other than for wall mounting, each measuring not more than 15 cm in length, 11 cm in width, and 3 cm in height (described in statistical reporting number 9032.10.0060)
9032.89.4000	Battery balancers designed for regulating voltage across batteries, other than for 6, 12 or 24 volt systems (described in statistical reporting number 9032.89.4000)
9032.89.6040	Water level and temperature control devices of a kind used in household appliances (described in statistical reporting number 9032.89.6040)
9032.89.6060	Flow and liquid level control instruments, each valued not over \$10 (described in statistical reporting number 9032.89.6060)
9032.89.6085	Printed circuit board assemblies designed to control the flow of paint in paint sprayers (described in statistical reporting number 9032.89.6085)
9032.90.6120	Thermostat covers (described in statistical reporting number 9032.90.6120)