

List 3 Round Eleven Section 301 Exclusions for China

HTS	Excluded Description
0304.61.0000	Tilapias, frozen, each weighing not more than 115 g
0508.00.0000	Shells of oysters (<i>Crassostrea angulata</i>)
1207.70.0075	Honeydew melon seeds
1209.91.6090	Hot pepper seeds, of a kind used for sowing
1209.91.8055	F1 hybrid pumpkin seeds, oval in shape, with a white outer husk, measuring not more than 10 mm, of a kind used for sowing
1209.91.8090	Eggplant seeds, of a kind used for sowing
1209.91.8090	Endive seeds, of a kind used for sowing
1209.91.8090	Gourd seeds, of a kind used for sowing
1209.91.8090	Tomatillo seeds, of a kind used for sowing
1605.10.2059	Crabmeat of red swimming crabs (<i>Portunus haanii</i>) packed fresh and pasteurized or frozen in airtight containers
2811.22.1000	Synthetic silica gel, in amorphous granules, of a kind used as a catalyst support
2907.15.1000	α -Naphthol (CAS number 90-15-3)
2912.19.3000	Glyoxal (CAS No. 107-22-2)
2914.50.3000	(2-Hydroxy-4-methoxyphenyl)phenylmethanone (CAS No. 131-57-7) (Oxybenzone (INN)) and (2-Hydroxy-4-octoxyphenyl)phenylmethanone (CAS No. 1843-05-6) (Octabenzene (INN))
2915.40.5050	2,2-Dichloroacetyl chloride (CAS No. 79-36-7)
2917.12.5000	Sodium adipate (1,4-butanedicarboxylic acid, disodium salt) (IUPAC name: disodium hexanedioate) (CAS No. 7486-38-6)
2922.29.8190	4-Aminophenol (CAS No. 123-30-8)
2924.21.1600	Diuron (IUPAC name: 3-(3,4-dichlorophenyl)-1,1-dimethylurea) (CAS No. 330-54-1)
2924.29.7100	2-((3-Fluoro-4-(methylcarbamoyl)-phenyl)amino)-2-methylpropanoic acid (CAS No. 1289942-)
2926.90.4300	3,4-Difluorobenzonitrile (CAS No. 64248-62-0)
2926.90.4801	Octocrylene (IUPAC name: 2-ethylhexyl 2-cyano-3,3-diphenylprop-2-enoate) (CAS No. 6197-30-4)
2926.90.5050	3-Cyclopentylacrylonitrile (IUPAC name: (E)-3-Cyclopentylprop-2-enenitrile) (CAS No. 591769-05-0)
2926.90.5050	Acetonitrile (CAS No. 75-05-8)
2929.90.5090	N-(n-Butyl)thiophosphoric triamide (IUPAC name: N-Diaminophosphinothiylbutan-1-amine) (CAS No. 94317-64-3)
2931.90.3000	(4-Chloro-2-fluoro-3-methoxyphenyl) boronic acid (CAS No. 944129-07-1)
2931.90.7000	2-Phosphonobutane-1,2,4-tricarboxylic acid and its salts (CAS #40372-66-5)
2934.10.9000	Clothianidin technical (CAS No. 210880-92-5) (IUPAC name: E-1-[(2-Chloro-1,3-thiazol-5-yl)methyl]-3-methyl-2-nitroguanidine)
2934.20.1500	2-Mercaptobenzothiazole (CAS No. 149-30-4)
3810.90.2000	Flux powder consisting wholly of inorganic substances, including but not limited to silicon dioxide, titanium oxide, manganese oxide, aluminum oxide, and calcium fluoride, for submerged arc welding
3913.90.2090	Chitosan (CAS No. 9012-76-4)
3923.10.9000	Boxes, cases, crates or similar articles of plastics certified under UN (United Nations) standard 4H2 as suitable for the conveyance of lithium ion batteries and equipment powered by lithium ion batteries
3925.90.0000	Parts of fences fabricated from profile shapes of heading 3916
3926.90.4590	Gaskets, washers and other seals (other than O-rings) of silicone plastic, each weighing at least 5 g but not more than 400 g

4009.11.0000	Hoses of vulcanized rubber other than hard rubber, not reinforced or otherwise combined with other materials, without fittings, each weighing at least 10 g but not more than 1,000 g and measuring at least 2 cm but not more than 500 cm in length
4009.31.0000	Hoses of vulcanized rubber other than hard rubber, reinforced or otherwise combined only with textile materials, without fittings
4009.41.0000	Hoses of vulcanized rubber other than hard rubber, reinforced or otherwise combined with materials other than metals or textiles, without fittings
4011.90.1010	New tubeless pneumatic tires of rubber having a "herring-bone" tread and a tire ply rating of 6R, measuring not more than 61 cm in outside diameter and at least 20.3 cm but not more than 25.4 cm in width, for mounting on a rim measuring 35.6 cm in diameter
4011.90.2010	New radial pneumatic tires of rubber, each with an 8 ply rating, measuring not more than 67 cm in outside diameter and at least 22 cm but not over 28 cm in width, suitable for mounting on a rim measuring 30.5 cm in diameter
4011.90.2010	New radial pneumatic tires of rubber, measuring 66 cm or more but not exceeding 82 cm in diameter, and 22 cm or more but not exceeding 39 cm in width, with steel internal carcass and sidewalls reinforced with three belts
4011.90.8010	New bias-ply pneumatic tires of rubber, with a 6 ply rating, each measuring at least 61 cm but not more than 62 cm in diameter, and at least 20 cm but not more than 31 cm in width, suitable for mounting on a rim measuring 30.5 cm in diameter
4016.91.0000	Compression molded floor mats for golf carts, of vulcanized rubber other than hard rubber or cellular rubber, each measuring not more than 1,038 mm by 605 mm
4016.99.6050	Grommets, vibration dampers, and similar protective separators, of molded ethylene-propylene-non-conjugated diene monomer rubber (EPDM), each weighing not more than 2.27 kg, of a kind used in motorcycles or personal watercraft (PWC)
4202.92.2000	Backpacks and duffel bags with an outer surface of a blend of hemp and organic cotton, each measuring not less than 38 cm by 30 cm by 15 cm and not more than 36 cm by 72 cm
4202.92.3120	Backpacks with outer surface of textile materials of man-made fibers, each measuring at least 35 cm but not more than 75 cm in height, at least 19 cm but not more than 34 cm in width, and at least 5 cm but not more than 26 cm in depth
4202.92.3131	Fishing tackle bags of man-made fibers, each measuring at least 5 cm but not more than 17 cm in width, at least 23 cm but not more than 27 cm in height and at least 37 cm but not more than 43 cm in depth, with a shoulder strap and carrying handles
4202.92.3131	Surfboard covers, each with an outer surface of polyester, weighing at least 0.85 kg but not more than 6 kg, measuring at least 150 cm but not more than 307 cm in height and at least 55 cm but not more than 66 cm in width
4202.92.3131	Tote bags with outer surface of man-made fibers, with handles, with printing on front and back, each bag measuring more than 20 cm but not more than 36 cm in width and more than 22 cm but not more than 39 cm in height, with a gusset measuring not more than 16 cm
4202.92.9100	Bags with outer surface of textile materials of man-made fibers, each with a base of plastics and a coil zipper, weighing 0.22 kg or more but not over 4.6 kg, shaped to fit powersports vehicles (including but not limited to off-road vehicles, all-terrain vehicles, snowmobiles and motorcycles)
4202.92.9100	Pouches and tool holsters of woven man-made fibers, each measuring at least 13 cm but not more than 19 cm in height, at least 4 cm but not more than 11 cm in width and at least 3 cm but not more than 5 cm in depth, valued not over \$16 each, designed to fit over the wearer's belt or attach to belt loops to provide hands-free carrying of mobile phones, tools, flashlights and articles of similar size
4202.99.9000	Gun cases (boots) of plastics, each with interior padding, dust-proof and water-resistant shell and steel brackets for mounting

4203.10.4095	Women's, girls', and infants' pants, skirts and dresses, of polyurethane-coated leather of swine or of polyurethane-coated composition leather of swine
4819.10.0040	Printed cartons, boxes or cases of corrugated paper or paperboard, other than sanitary food or beverage containers
4820.10.2060	Notebooks of paper or paperboard, each incorporating a plastic toy building block on the cover, measuring at least 13 cm but not more than 16 cm on the short side, at least 15 cm but not more than 22 cm on the long side and at least 1 cm but not more than 3 cm in thickness, with at least 192 but no more than 352 ruled or blank pages
4823.70.0020	Plates, bowls or cups of molded or pressed bamboo pulp, each weighing at least 3 g but not more than 92 g
4823.70.0040	Clamshell containers, pizza pans, lids, compartmentalized and other trays of molded or pressed bamboo pulp, each weighing at least 3 g but not more than 95 g
5108.10.8000	Yarn of cashmere or camel hair, carded but not combed, not put up for retail sale
5501.20.0000	Polyester filament tow, weighing at least 225 ktex but not more than 275 ktex
5501.40.0000	Polypropylene fiber tow weighing at least 225 ktex but not more than 275 ktex
5903.20.2000	Textile fabrics of woven polyester or of a blend of cotton and polyester, coated on one side with expanded polyurethane which comprises more than 70 percent of the total weight of the product, the entire thickness of the fabric measuring at least 0.8 mm but not more than 1.22 mm in thickness and weighing at least 350 g/m ² or more but not more than 425 g/m ²
6006.32.0080	Circular single knitted fabric, containing by weight 96 percent polyester and 4 percent spandex, dyed
6802.91.1500	Freestanding bathtubs carved from solid marble blocks, not laminated or glued, each with dimensions not over 215 cm by 125 cm by 70 cm and weighing not more than 1,600 kg
6802.91.1500	Sinks and sink pedestals of marble for bathroom and kitchen use, each measuring not more than 110 cm by 95 cm by 95 cm and weighing not more than 415 kg
6802.93.0090	Worked monumental or building stone articles of genuine geological granite, birdbaths, benches, fountains, and fire pits
6802.99.0060	Sandstone known as brown wave, of a kind used in outdoor living spaces, containing one textured side and up to four chiseled edges with a density of 2,750 kg/m ³
6802.99.0060	Sandstone with a flamed finish on one side and a length of 200 mm or more but not over 3,100 mm, a width of 100 mm or more but not over 1,380 mm and a thickness of 30 mm or more but not over 180 mm
6810.99.0080	Figurines and statuettes of agglomerated stone, each measuring at least 100 mm but not more than 310 mm in height and weighing at least 0.1 kg but not more than 2.1 kg
6815.10.0100	Synthetic graphite, in the form of rounds measuring at least 5 cm but not more than 153 cm in diameter and at least 25 cm but not more than 204 cm in length, or rectangles measuring at least 40 cm but not more than 61 cm in width, at least 40 cm but not more than 94 cm in height, and 152 cm or more but not more than 280 cm in length
6909.12.0000	Articles of ceramics, other than porcelain or china, having a hardness equivalent of 9 or more on the Mohs scale, machined to shape, weighing not more than 2.4 kg and measuring not more than 45.5 cm by 3.1 cm by 8.9 cm
6909.19.5095	Inert ceramic rings and spheres, of a kind used for bed grading in mixed-layered filtering and purification columns
7007.19.0000	Screen protectors of tempered safety glass, with adhesive on one side, in rectangular sheets having rounded corners, each measuring at least 55 mm by 120 mm but no more than 212 mm by 278 mm and at least 0.51 mm but no more than 0.55 mm in thickness
7007.19.0000	Sheets of tempered safety glass, coated with silicone oxide, having a surface area of less than 2.5 m ² , designed to be placed over solar cell panels for protection from external damage

7007.21.1010	Windshields of laminated safety glass, of a size and shape for vehicles, each weighing at least 10.9 kg but not over 15.4 kg
7009.10.0000	Rear-view mirrors for vehicles, composed of stainless steel, aluminum, glass filled nylon, polyethylene, and acrylonitrile-butadiene-styrene, each weighing at least 500 g but not more than 1 kg, with mirrors measuring at least 180 mm but not more than 400 mm in length
7009.10.0000	Rear-view mirrors for vehicles, each consisting of a multi-curvature convex glass mirror, a steel case and a heating element
7009.10.0000	Replacement kits for rear-view mirrors for vehicles, each consisting of a multi-curvature convex mirror, a gasket and a heating element
7308.30.1000	Windows of stainless steel incorporating tempered glass, each fitted with a rubber gasket that provides a water-tight seal when closed, designed for installation in ships and boats of
7309.00.0030	Steel tanks, each of a capacity of at least 477 liters but not over 23,848 liters and weighing at least 100 kg but not more than 2,250 kg, whether or not lined or heat insulated, but not fitted with mechanical or thermal equipment
7310.10.0010	Square-shaped barrels of stainless steel, each with slatted sides and a maximum capacity of 228 liters
7315.20.1000	Skid chains of steel, with links measuring not over 8 mm in diameter, to fit off-road vehicle tires measuring 63 cm or more but not over 67 cm in diameter
7321.90.1000	Steel cooking grates comprising parts of stoves and ranges, each weighing not less than 1 kg, measuring not less than 40 cm in length, not less than 48 cm in width, and not less than 5 cm in height
7323.99.9080	Bird feeders, predominantly of iron or steel, with glass elements, each feeder measuring at least 25 cm but not more than 36 cm in height, and weighing at least 0.6 kg but not more than 1.4 kg
7324.90.0000	Parts of showers, comprising shower wand adjustable slide bars, of stainless steel, with or without finishes of other metals, each weighing 0.44 kg or less, measuring at least 48.3 cm but not more than 91.5 cm in length and at least 1.9 cm but not more than 2.6 cm in diameter
7324.90.0000	Shower arms of stainless steel, with or without finishes of other metals, threaded at both ends, each weighing not less than 0.08 kg but not more than 0.35 kg, measuring at least 15 cm but not more than 64 cm in length and not more than 2 cm in diameter
7326.90.8688	Carabiners of stainless steel, not suitable for climbing applications
7326.90.8688	Housings of steel designed for oil or natural gas wellheads, each with threaded or welded bottom and threaded top, each weighing at least 284 kg but not more than 1,200 kg, measuring at least 52 cm but not more than 105 cm in length, at least 42 cm but not more than 60 cm in outer diameter, with a bore diameter of not less than 20 cm
7326.90.8688	Tubing heads of steel for oil or natural gas wellheads, each measuring at least 39 cm but not more than 107 cm in length, at least 57 cm but not more than 78 cm in outer diameter, with a bore diameter of not less than 13 cm
7419.99.5010	Escutcheons of brass, with or without other metal finishes, each weighing not more than 0.5 kg, measuring not more than 23 cm by 23 cm by 3 cm, designed as trim around faucets or shower fixtures
7419.99.5010	Faucet parts, of brass, designed for holding the aerator, each not over 4 cm in height
7419.99.5010	Shower arms of brass, each for connecting the showerhead to the water supply
7616.99.5190	Carabiners of aluminum, not suitable for climbing applications
7907.00.6000	Key rings of zinc, with leather adornment
8207.50.2070	Kits of auger bits for woodworking of high carbon steel (with cutting part containing by weight over 0.2 percent of chromium, molybdenum, or tungsten or over 0.1 percent of vanadium), each bit measuring not less than 0.95 cm but not more than 3.81 cm in diameter and not less than 15.24 cm but not more than 45.72 cm in length

8207.50.6000	Kits of spade bit blades of high carbon steel (with cutting part not containing by weight over 0.2 percent of chromium, molybdenum, or tungsten or over 0.1 percent of vanadium), each bit measuring at least 0.635 cm but not more than 3.81 cm in diameter and at least 15.24 cm but not more than 45.72 cm in length
8302.20.0000	Castors with mountings of steel with wheels of rubber or plastic, each having a wheel diameter (including tires) of more than 60 mm but less than 210 mm
8302.30.3060	Mountings and fittings suitable for motor vehicles of iron or steel, of aluminum or of zinc, other than pneumatic cylinders
8302.49.6055	Cleats and chocks of stainless steel for boats and ships
8302.49.6085	Screen door cross bars of aluminum, each adjustable, measuring at least 53 cm but not more than 74 cm in length, weighing not more than 0.6 kg, with polypropylene end caps
8409.91.5085	Pistons of cast aluminum, of a kind used in spark-ignition internal combustion piston engines for vehicles of heading 8703, each measuring 73 mm in diameter and 45 mm in height
8409.91.9990	Cylinder heads of aluminum for motorcycle engines, each weighing at least 3.6 kg but not more than 6.4 kg
8413.30.9090	Cooling medium pumps for internal combustion piston engines of the motor vehicles of headings 8703 or 8704
8414.80.1680	Stationary air compressors (not reciprocating, not rotary), each powered by 12 V DC motor, with maximum output pressure of 1.04 MPa and maximum output volume of 57 liters/min, weighing not more than 6 kg, with braided output leader hose and one-way check valve attached to the cylinder head
8425.42.0000	Hydraulic jacks of a kind for raising vehicles, with a lifting capacity of not more than 550 kg
8425.42.0000	Hydraulic lifts of steel weighing not more than 30 kg, comprising a base, two lift arms and a hydraulic bottle jack, with a weight limit of not more than 250 kg
8425.49.0000	Screw jacks and scissor jacks, each comprising a base, two lift arms and adjustable wheel pads, weighing at least 22 kg but not more than 42 kg, with a weight limit of not more than 342 kg
8465.91.0064	Bandsaws for working wood, bench top, each valued under \$1,000, with 115 V motor, measuring not more than 88 cm in height, not more than 54 cm in width and not more than 42 cm in depth, weighing not more than 36 kg with a cutting capacity not exceeding 36 cm in width
8465.91.0064	Bandsaws for working wood, floor standing, each valued under \$1,000, with 115 V motor, measuring not more than 190 cm in height, at least 63 cm but not more than 88 cm in width and at least 63 cm but not more than 66 cm in depth, weighing at least 99 kg but not more than 130 kg with a cutting capacity not exceeding 36 cm in width
8465.91.0064	Bandsaws for working wood, valued under \$1,000 each, floor standing, with 115 V motor, measuring not over 190 cm in height, at least 63 cm but not more than 88 cm in width and at least 63 cm but not more than 66 cm in depth, weighing at least 99 kg but not more than 130 kg with a cutting capacity not exceeding 36 cm in width
8479.89.9499	Straps for securing articles, each consisting of a polyester webbing strap of a width not exceeding 26 mm with steel hooks at the ends and a ratchet mechanism for tightening the strap, in lengths not over 2.5 m
8481.80.3055	Handwheel-operated gate valves of forged steel, each measuring at least 37 cm but not more than 102 cm in width (at the circular connector flanges) and at least 55 cm but not more than 288 cm in height (from the bottom of the valve to the top of the handwheel), having a bore measuring at least 5 cm but not more than 18 cm in diameter, weighing at least 79 kg but not more than 3,015 kg
8483.10.1030	Camshafts designed for use solely or principally with spark-ignition internal combustion piston engines for off-road vehicles and snowmobiles

8483.10.3050	Crankshafts designed for use with diesel engines having a displacement of not more than 12 liters
8483.90.5090	Toothed wheels and sprockets other than chain sprockets for motorcycles, off-road vehicles and snowmobiles constituting an integral component of an engine or motor
8501.40.2040	Single phase AC electric motors (other than gear motors), of an output of 56 W or more but not exceeding 69 W, each measuring no more than 9 cm in length and no more than 11.5 cm in diameter, weighing no more than 2 kg, in a housing of base metals, with a switch
8501.40.4040	Single-phase AC electric motors incorporating permanent split capacitors, each of an output range of 367 W or more but not exceeding 565 W, operating at not less than 115 V of alternating current (VAC) but not more than 230 VAC, capable of operating while submerged in water, each weighing at least 7 kg but not more than 11 kg, measuring not more than 10 cm in diameter and at least 22 cm but not exceeding 34 cm in length
8501.40.6040	Single-phase AC electric motors, other than gear motors, incorporating permanent split capacitors, each of an output range of 746 W or more but not exceeding 1.13 kW, operating at not less than 115 V of alternating current (VAC) but not more than 250 VAC, capable of operating while submerged in water, each weighing at least 9 kg but not more than 12.5 kg, measuring not more than 10 cm in diameter and at least 25 cm but not exceeding 36 cm in length
8504.40.9550	Battery chargers designed to charge the batteries in electrically powered golf carts and similar utility vehicles for a voltage not exceeding 48 V, measuring no more than 20 cm in width, 30 cm in length, and 15 cm in height
8504.40.9550	Static converters, each with input voltage range of 10 V or more but not exceeding 26 V and a power output range of at least 5 A but not more than 240 A, weighing not more than 23 kg
8504.50.8000	Inductors, each with inductance of 22 microhenrys (μH), a tolerance of no greater than 20 percent, with a DC resistance of 198 milliohms ($\text{m}\Omega$) and a DC current of 1.9 A
8504.50.8000	Inductors, each with inductance of 220 microhenrys (μH), a tolerance of no greater than 20 percent, with a DC resistance of 550 milliohms ($\text{m}\Omega$) and a DC current of 510 milliamps (mA)
8504.50.8000	Inductors, each with inductance of 470 microhenrys (μH), a tolerance of no greater than 20 percent, with a DC resistance of 700 milliohms ($\text{m}\Omega$) and a DC current of 540 milliamps (mA)
8507.10.0030	Lead-acid storage batteries, 12 V, of a kind used in starting piston engines, each measuring not more than 167 cm in height, at least 91 cm but not more than 92 cm in width and weighing at least 4.8 kg but not more than 5.3 kg
8511.30.0080	Ignition coils for spark-ignition or compression-ignition engines of a kind designed to be mounted in powersports vehicles, including off-road vehicles, all-terrain vehicles, snowmobiles and motorcycles
8512.20.2040	Lighting equipment designed for illuminating the interior of the vehicles of subheading 8701.20 or heading 8702, 8703, 8704, 8705 or 8711 incorporating LED lamps, each measuring not more than 128 mm by 75 mm by 36 mm
8525.80.3010	Color television cameras of a kind used with vehicle displays
8527.29.4000	Radiobroadcast receiver kits, each comprising a radiobroadcast receiver not capable of operating without an external source of power, the foregoing of a kind used in motor vehicles, not combined with sound recording or reproducing apparatus, incorporating an FM only or AM/FM only tuner, two speakers measuring not more than 135 mm in diameter, a 45 W 4-channel amplifier and an external antenna
8531.20.0020	Indicator panels incorporating segmented liquid crystal devices (LCDs) suitable for use in motor vehicles and designed to display a limited number of characters or icons, each panel measuring not more than 99 mm in width and not more than 61 mm in height
8531.20.0040	Indicator panels incorporating LEDs, designed for use in medical infusion equipment

8534.00.0020	Printed circuit boards, with a base of glass reinforced epoxy laminate material that is compliant with NEMA grade FR-4 fire resistance, not flexible, with 10 layers, designed for use in a flow meter, and measuring not more than 6.35 cm by 6.35 cm by 0.1575 cm
8534.00.0095	Printed circuit board, 2 layers, LED left-handed tail light, of FR-4 woven fiberglass cloth with a flame resistant epoxy resin binder with a glass transition temperature of 150 degrees C, with not more than 0.03 kg of copper
8534.00.0095	Printed circuit board, 2 layers, LED left-handed tail stop light, of FR-4 woven fiberglass cloth with a flame resistant epoxy resin binder, with not more than 0.03 kg of copper
8534.00.0095	Printed circuit board, 2 layers, LED right-handed tail stop light, of FR-4 woven fiberglass cloth with a flame resistant epoxy resin binder, with not more than 0.03 kg of copper
8534.00.0095	Printed circuit board, 2 layers, overhead council assembly of FR-4 woven fiberglass cloth with a flame resistant epoxy resin binder, with not more than 0.03 kg of copper, with lead free HASL finish
8534.00.0095	Printed circuit board, 2 layers, overhead council unit, of FR-4 woven fiberglass cloth with a flame resistant epoxy resin binder, with lead free HASL finish
8534.00.0095	Printed circuit board, 2 layers, with high- or low-side driver pulse width modulation, of FR-4 woven fiberglass cloth with a flame resistant epoxy resin binder with a glass transition temperature of 150 degrees C with not more than 0.03 kg of copper
8534.00.0095	Printed circuit board, 4 layers, rear view mirror utilized, of FR-4 woven fiberglass cloth with a flame resistant epoxy resin binder, with not more than 0.03 kg of copper
8534.00.0095	Printed circuit boards, formed as 2 layers, DS video mirror of FR-4 woven fiberglass cloth with a flame resistant epoxy resin binder with a glass transition temperature of 150 degrees C with not more than 0.03 kg of copper
8543.70.9100	Digital sound processing apparatus capable of connecting to a wired or wireless network for the mixing of sound, each capable of mixing 16, 24, 32 or 64 channel, each measuring not more than 17 cm in height, not more than 60 cm in depth, and not more than 83 cm in width
8544.42.9090	Electric conductors, for a voltage not exceeding 1,000 V, with stranded 18-gauge copper wire and SPT-2 outer insulation, with either a 2-prong polarized plug or a 3-prong grounded plug on one end, such plugs with an integrated non-replaceable fuse, such conductors measuring at least 210 cm but not more than 250 cm in length
8708.10.3050	Bumpers of steel or aluminum, other than stampings, for off-road vehicles of headings 8701 to 8705
8708.29.5060	Vent insulators to fit a standard vent opening of 35.56 cm by 35.56 cm on a recreational vehicle, each composed of foam encased in polyester fleece fabric, whether or not also featuring reflective foil
8708.70.4560	Road wheels of steel for vehicles of heading 8703, each measuring at least 32 cm but not more than 37 cm in diameter, at least 11 cm but not more than 21 cm in width and weighing at least 5.2 kg but not over 6.7 kg
8708.70.4560	Road wheels of steel for vehicles of heading 8703, each measuring at least 37 cm but not more than 46 cm in diameter and at least 19 cm but not over 26 cm in width
8708.70.6060	Wheel spacers of aluminum for the motor vehicles of heading 8703, measuring at least 25 mm but not more than 45 mm in thickness
8708.80.6590	Parts of suspension systems of off-road vehicles of headings 8701 through 8705 and snowmobiles of heading 8703
8708.80.6590	Torque rods, also known as torque arms, radius rods or radius arms)
8708.91.5000	Radiators of aluminum, each measuring at least 335 mm but not more than 630 mm in length, at least 167.5 mm but not more than 355 mm in width, and at least 37.5 mm but not more than 60 mm in height
8708.92.5000	Mufflers and exhaust pipes for all-terrain vehicles (ATVs) and snowmobiles of heading 8703

8708.94.5000	Steering boxes and steering columns of steel for all-terrain vehicles (ATVs) of heading 8703 and other off-road vehicles
8708.94.7000	Parts of the motor vehicles of headings 8701, 8702, 8704 and 8705, consisting of housings of cast iron for steering gears, each weighing not more than 20 kg, measuring at least 11 cm but not more than 29 cm in length, at least 9 cm but not more than 19 cm in width, and at least 14 cm but not more than 24 cm in height
8708.94.7000	Steering cylinder heads of cast iron for motor vehicles of chapter 87, each weighing at least 1 kg but not more than 3 kg
8708.94.7550	Housing covers (with or without bearings) of carbon steel for steering gears of the motor vehicles of headings 8701 to 8705 (except for tractors other than road tractors)
8708.94.7550	Pitman arm retainers of carbon steel designed for steering gears for the vehicles of heading 8701, 8702, 8704, or 8705, other than steering gears for tractors for agricultural use but including those for road tractors
8708.99.6890	Castings of aluminum for hub lock assemblies of motor vehicles of heading 8703
8708.99.6890	Shift lever weldments, sprockets, shafts, bearing carriers, and rod shifters, all the foregoing being parts of power trains for the motor vehicles of headings 8701 to 8705
8708.99.8180	Covers for automobile seats or passenger compartments, of textile fabric, with or without fastening hardware, presented separately or in sets put up for retail sale
8708.99.8180	Intercooler pipes of cast aluminum, each weighing at least 0.37 kg but not more than 0.643 kg
8708.99.8180	Racks designed to fit into receiver hitches of vehicles of headings 8701 to 8705, for transporting bicycles
8708.99.8180	Trailer hitch kits of alloy steel or carbon steel, for the vehicles of headings 8701 to 8705, other than tractors, except including road tractors
8712.00.4800	Bicycles, including mountain-type, with drop bar, tubeless, folding
8716.40.0000	Trailers with steel or aluminum frames, single axle, each measuring at least 1.5 m but not more than 2.5 m in width, at least 2.4 m but not more than 5.8 m in length, and weighing at least 110 kg but not more than 730 kg
8716.90.3000	Castors, each comprising a polyurethane tread over a polypropylene hub, measuring at least 7.5 cm but not more than 20.5 cm in diameter and at least 2.5 cm but not more than 5.5 cm in width, for use with retail shopping carts, material handling carts, light industrial carts, baker carts, laboratory carts, medical carts or pharmaceutical carts
9002.11.9000	Mounted camera lenses, each with a M12 mount configuration, with an 8.46 mm sensor format and focal lengths between 2.8 mm and 16.0 mm, focal ratio (F/No) of 1.4 or greater but not exceeding 6.6 and a fixed iris
9401.20.0000	Seats of a kind used for automobiles, not reclining, incorporating padding of polymeric foam and seat covers of PVC
9403.20.0081	Adjustable wire shelving units of steel, other than for household use, comprising vertical poles, foot caps or casters, clips and shelves, each when fully assembled measuring at least 35 cm or more but not more than 183 cm in width, at least 35 cm but not more than 77 cm in depth, and at least 137 cm but not more than 183 cm in height
9403.20.0081	Storage racks of steel, powder-coated, designed to hang from overhead support, each weighing not more than 37 kg, measuring not more than 123 cm in width, not more than 123 cm in height and not more than 245 cm in length
9403.20.0090	Shelving units of chrome plated steel, each consisting of wire shelves measuring at least 35 cm but not more than 62 cm in width and at least 61 cm but not more than 183 cm in length and supporting posts, with leveling feet, measuring not more than 30 cm in length
9403.60.8081	Cabinets of wood with glass fronts, each measuring at least 208 cm but not more than 234 cm in height, at least 86 cm but no more than 128 cm in width and at least 40 cm but not more than 49 cm in depth

9403.60.8081	Cabinets of wood with glass fronts, each measuring at least 91 cm but not more than 117 cm in height, at least 165 cm but no more than 216 cm in width and at least 38 cm but not more than 59 cm in depth
9403.89.6015	Outdoor tables of artificial stone, each measuring no more than 93 cm by 93 cm by 63 cm, with a built-in gas-burning fire pit
9403.89.6020	Sets of rectangular laundry organizers consisting of at least six, but not more than nine collapsible hampers of ethylene-vinyl acetate (EVA) fabric, each with a drawstring top, an exterior zip pocket, and rope handles, designed to stand on the floor and fold up when not in use
9403.90.7080	Parts of counters, racks, display cases, and similar fixtures of wood other than cane, osier, bamboo or similar materials
9403.90.8041	Parts of counters, racks, display cases, and similar fixtures of base metal, other than welded wire rack decking
9405.20.8010)	Lamps with bases of agglomerated stone that are figurines, each measuring at least 45 cm but not more than 77 cm in height, weighing at least 1.3 kg but not more than 2.8 kg, with a decorated fabric shade
9405.20.8010	LED lamps other than of base metal, each with height adjustable from at least 19 cm to not more than 38 cm, with touch switch controlling power, brightness and three color modes (warm, bright and natural daylight illumination), 5 V, 2.1 A USB charging port, and digital LCD display featuring time, date, and temperature display
9405.40.8200	LED backlight modules, each measuring at least 90 mm but not more than 105 mm in length and at least 45 mm but not more than 55 mm in width
9405.40.8440	Flameless pillar candles with LED lamps powered by batteries, each measuring at least 7.6 cm but not more than 20 cm in diameter and having a wax exterior
8414.59.6540	Ventilation fans for motor vehicles, consisting of a 12 V DC non-reversible multiple speed electric motor drawing 5 A, with axial fan blade, electric keypad and circuit board and wire mesh screen, measuring no more than 36 cm by 36 cm
8414.59.6540	Ventilation fans for motor vehicles, consisting of a 12 V DC non-reversible multiple speed electric motor drawing 5 A, with axial fan blade, keypad and circuit board and wire mesh screen, measuring no more than 36 cm by 36 cm
8414.59.6540	Ventilation fans for motor vehicles, consisting of a 12 V DC non-reversible multiple speed electric motor drawing 5 A, with axial fan blade, keypad or remote control and circuit board and wire mesh screen, measuring no more than 36 cm by 36 cm
8414.59.6540	Ventilation fans for motor vehicles, consisting of a 12 V DC non-reversible multiple speed electric motor drawing 5 A, with axial fan blade, network control system and wire mesh screen, measuring no more than 36 cm by 36 cm
8414.59.6540	Ventilation fans for motor vehicles, consisting of a 12 V DC reversible multiple speed electric motor drawing 5 A, with axial fan blade, electric keypad and circuit board and wire mesh screen, measuring no more than 36 cm by 36 cm