

**Exclusion Descriptions Expiring April 18, 2020**

Pumps designed for countertop appliances for serving beer, the foregoing that control the level of carbonation by means of sonic waves (of HTS 8413.19.0000)

Water oxidizers and chlorinators (of HTS 8421.21.0000)

Continuous action elevators and conveyors, designed to convey mineral materials (of HTS 8428.33.0000)

Parts of drill sharpening machines (of HTS 8466.93.9885)

Outer shells of hydraulic accumulators, of iron or non-alloy steel, cylindrical with hemispherical heads on each end (of HTS 8479.90.9496)

Parts of mechanical awnings and shades (of HTS 8479.90.9496)

Pressure regulators of brass or bronze, whether high or low inlet type, having a rated flow rate of 55,000 - 150,000 BTU/hr, maximum inlet pressure of 0.17 MPa to 1.72 MPa, inlet connection with POL or thread type of fitting (of HTS 8481.10.0090)

Push pins and C-poles of steel, designed for use in variable force solenoid valves (of HTS 8481.90.9040)

Ball bearings of a width not exceeding 30 mm (of HTS 8482.10.5032)

Inductor baseplates of aluminum, each with a length measuring 149.20 mm or more but not over 275 mm, with a width measuring 119.40 mm or more but not over 232 mm and with a depth of 10.50 mm or more but not over 19 mm, with a weight of 0.48 kg or more but not over 3.2 kg (of HTS 8504.90.9690)

Parts of soldering irons and soldering machines (of HTS 8515.90.4000)

Motor vehicle gear shift switch assemblies, comprised of a plunger, connector and gear shift lever (of HTS 8536.50.9065)

Pressure switches designed for use in heat pumps and air-conditioning condensers having a rating of 1.90 megapascals or more but not over 4.55 megapascals (of HTS 8536.50.9065)